JR-6 / JR-6A DUAL SPEED SPINNER MAGNETOMETERS



The world's most sensitive and accurate instruments for measurement of remanent magnetization of rocks based on classical (non-cryogenic) principle. Two rotation speeds available, the higher one enabling the maximum sensitivity to be reached, and the lower one enabling the soft specimens to be measured. Instruments enable measurement even of very weekly magnetic sedimentary rocks including limestone.

JR-6 / JR-6A Models

The **JR-6** version is destined for simple measurement of remanent magnetization with manual change of measuring positions of a specimen. According to the accuracy demands, one can measure the specimen in two, four, or six positions.

The **JR-6A (automated)** version is destined for rapid and accurate measurement of remanent magnetization. The specimen is manually only inserted into the specimen holder and the changes of positions in the holder in order to get complete vector are made automatically by the instrument.

General Description

The **JR-6/JR-6A** magnetometer consists of an integrated pick-up and measurement control unit, and a power supply unit. All functions are microprocessor-controlled. The microprocessor controls measurement, carries out digital filtration of the signal, controls and tests the speed of specimen rotation. The JR-6/JR-6A automatically executes tests for erroneous conditions. The measurement process is fully controlled by a PC notebook or desktop.

Typical JR-6 / JR-6A Applications

Palaeomagnetism: The changes of Earth's magnetic field in geological history can be investigated through the measurement of rock's remanent magnetization and the investigation of its stability. These data are also applicable to dating the age of rocks, to solving some tectonic problems or particular terrains (rotations of terrains, microplates), to dating the developments of mineralizations of ore deposits and to many geological problems.

Archaeomagnetism: The changes of the Earth's magnetic field in human history can also be investigated. These investigations are mostly applicable to dating archeological materials.

Magnetometry: In the interpretation of ground or airborne magnetometric measurements it is useful to know whether the rock's magnetization is due to its induced or remanent component. Investigation of remanent magnetization can help to solve this problem.

Mineralogy: Using special capsule enabling smaller irregular specimens to be measured, impurities of ferromagnetic grains in paraor diamagnetic minerals can be investigated.

Operating Principle

Rock specimen rotates at a constant angular speed in the pickup unit inside a pair of Helmholtz coils. In the coils an AC voltage is induced whose amplitude and phase depend on magnitude and direction of the remanent magnetization vector.



JR-6 / JR-6A DUAL SPEED SPINNER MAGNETOMETERS

Technical specifications

Sensitivity: Measuring range: Speed of rotation: Accuracy of absolute calibration Dimensions, mass: Pick-up Unit: Power Supply Unit: Power requirements: 2.4 x 10⁻⁶ A/m (high speed) up 12500 A/m 87.7 rps and 16.7 rps ±3 %

310 × 190 × 185 mm, 24 kg 200 × 160 × 120 mm, 2.5 kg 100, 120, 230 and 240 V, 50/60 Hz, 40 VA

Main features

High sensitivity 2.4 x 10⁻⁶ A/m Two speeds of rotation Automatic change of sample position (JR-6A only) Triple permalloy shielding of measuring coils Rapid measurement of remanent magnetization Sophisticated software support

Specimens to be measured

Cylinders (regularly shaped specimens)	
Diameter	25.4 ± 1 mm
Length	22.0 ± 1 mm
Cubes	23 x 23 x 23 mm
	20 x 20 x 20 mm

JR-6A Spinner Magnetometer Comprising

JR-6A Pick-up Unit with Automatic Sample Position Manipulator JR-6A Power Supply Unit Automatic Cylindrical Specimen Holders (2 pcs) Set of Specimen Holders for Manual Mode (4 pcs) Cylindrical and Cubic Calibration Standards Set of Spare Parts Set of Interconnecting Cables REMA6W Software REMASOFT Software User's Manual



AGIC®

JR-6 Spinner Magnetometer Comprising

JR-6 Pick-up Unit JR-6 Power Supply Unit Set of Specimen Holders (4 pcs) Cylindrical and Cubic Calibration Standards Set of Spare Parts Set of Interconnecting Cables REMA6W Software REMASOFT Software User's Manual

AGICO, Inc.

Advanced Geoscience Instruments Company Ječná 29a, CZ – 621 00 Brno, Czech Republic

Tel.: +420 511 116 303 Fax.: +420 541 634 328 E-mail: agico@agico.cz Web: www.agico.com